Amendment Dated: November 8, 2004 Reply to Office Action of September 29, 2004

Express Mail Label: EV487233497US

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the above-captioned patent application:

Listing of Claims:

1. (Withdrawn) In an enclosed mobile container having a refrigeration unit for providing conditioned air into a mixing chamber located at one end of the container, a method for controlling the ripening of perishable produce being transported in the container that includes the steps of:

stacking air penetratable cartons containing said produce in rows adjacent to both sidewalls of the container to establish a supply air plenum chamber between each sidewall and a row of said cartons and establishing a return air aisle between two rows of cartons so that the aisle extends down the center of the container,

delivering a high volume of supply air into each plenum chamber to pressurize the chamber whereby the supply air is forced through the air penetratable cartons in heat transfer relationship with the produce stored in said cartons,

activating a gas generator at the start of a ripening cycle to add a ripening agent into the supply air,

after a predetermined period of time, terminating said ripening cycle by discontinuing the step of adding a ripening agent and at that time opening a normally closed fresh air exchanger to vent the ripening agent to ambient, and subsequently closing the fresh air exchanger when the ripening agent has been vented to ambient.

- 2. (Withdrawn) The method of claim 1 that includes the further step of closing moisture drains mounted in the container during said ripening cycle.
- 3. (Withdrawn) The method of claim 1 that includes the further step of mounting the gas generator in said mixing chamber.

Amendment Dated: November 8, 2004

Reply to Office Action of September 29, 2004

Express Mail Label: EV487233497US

4. (Withdrawn) The method of claim 1 that includes the further step of mounting a plurality of fan units in a stack within the mixing chamber at an entrance to each plenum chamber for delivering a high volume rate of air into each plenum chamber sufficient to force the supply air through said cartons.

- 5. (Withdrawn) The method of claim 4 including the further step of activating the fan units in a given order.
- 6. (Withdrawn) The method of claim 1 including the further step of automatically controlling the opening and closing of said fresh air exchanger.
- 7. (Withdrawn) The method of claim 2 including the further step of automatically controlling the opening and closing of said drains.
- 8. (Withdrawn) The method of claim 4 wherein said fan units deliver 10,000 CFM or more supply air to said container.
- 9. (Currently Amended) Apparatus for closely controlling the temperature of perishable goods in a mobile container having a refrigeration unit for delivering conditioned air into a mixing chamber located adjacent the front wall of the container, said apparatus including:

a pair of supply air plenum chambers extending rearwardly from the mixing chamber toward the rear of the container along the sidewalls of the container that are arranged to receive supply air from said mixing chamber, one wall of each plenum being spaced apart from an adjacent side wall of said container and being formed by a stacked row of air permeable cartons containing said perishable produce,

fan means for delivering supply air from said mixing chamber into said plenum chambers at a volume rate of flow that is high enough to force the supply air into heat transfer relation with said produce contained in said cartons,

Amendment Dated: November 8, 2004

Express Mail Label: EV487233497US

Reply to Office Action of September 29, 2004

a gas generator located within the mixing chamber for introducing a ripening agent into the conditioned air at the beginning of a ripening cycle,

a fresh air exchanger unit which is normally in a closed condition to retain the conditioned air within said container during said ripening cycle and to exchange conditioned air with ambient air when placed in an open condition at the conclusion of said ripening cycle, and

control means for activating the gas generator at the beginning of a ripening cycle and for <u>automatically</u> deactivating the gas generator at the end of a ripening cycle; and

control means for determining when said gas generator is deactivated and responsively and automatically placing the fresh air exchanger unit in an open condition for a given period of time to vent the ripening agent from said container and automatically closing the fresh air exchanger when the ripening agent has been vented to ambient.

- 10. (Original) The apparatus of claim 9 wherein said fan means includes a series of fan units mounted in vertically aligned stacks at an entrance to each supply air chamber.
- 11. (Original) The apparatus of claim 10 wherein said mixing chamber contains a return air inlet through which conditioned air within the container is drawn by said fan means back into the mixing chamber.
- 12. (Original) The apparatus of claim 9 wherein each plenum chamber further includes a horizontal pressure bar secured to an adjacent side wall of the container and a movable vertical pressure bar for adjusting the length of the plenum chamber.

Amendment Dated: November 8, 2004 Reply to Office Action of September 29, 2004

Express Mail Label: EV487233497US

13. (Previously Presented) The apparatus of claim 9 that further includes drain means mounted in the floor of the container that is connected to the control means for placing the drain means in a closed position wherein moisture is maintained within the container during a ripening cycle and an open position wherein moisture in the container is released to the surrounding atmosphere.

- 14. (Original) The apparatus of claim 13 wherein said drain means further include a plurality of drains, each drain having remotely controlled drain valves for opening and closing said drain.
- 15. (Original) The apparatus of claim 10 wherein said fan means are connected to said control means which is programmed to activate the fan units in a given order.